

CAMPGROUND REGULATIONS

09.8 CAMPGROUND REGULATIONS

09.8.1 Scope and Purpose

(1) These regulations are in addition to, or where more strict, supersede, the requirements set forth in the State Sanitary Code under Article 8.

(2) The requirements hereinafter described are minimums for properly installed facilities maintained in a sanitary condition and functioning correctly.

09.8.2 Sanitary Facilities and Fixtures

(1) A separate wash/toilet room shall be maintained for each sex.

(2) A wash/toilet room shall not contain more than four (4) toilets, eight (8) lavatories, four (4) showers or three (3) urinals.

(3) Each wash/toilet room shall be sited in a properly constructed weathertight building with an impervious flooring surface. There shall be adequate provisions for the admission of light and air and the exclusion of insects. Where there are not ventilating windows in two outside walls, provisions shall be made for forced air ventilation; in no case shall available window ventilation be less than three (3) square feet per toilet.

(4) Lights illuminating entrances and exits and at least one centrally located ceiling light shall be operating during the hours of darkness. The switch controls for these minimum lights shall be accessible only to campground employees.

(5) The following are the minimum requirements for sanitary fixtures:

a. Toilets

The first twenty (20) sites, or fraction thereof, two (2) toilets of each sex. Each additional twenty (20) sites or fraction thereof, one toilet for each sex.

b. Urinals (males)

For each twenty sites, or fraction thereof, one (1) urinal. For campgrounds with less than ten

(10) sites, urinals are not required.

c. Lavatories

The first twenty (20) sites or fraction thereof, two (2) for each sex. Each additional twenty (20) sites or fraction thereof, one (1) lavatory for each sex.

d. Showers

The first twenty (20) sites or fraction thereof, two (2) for each sex. Each additional twenty (20) sites, or fraction thereof, one (1) shower for each sex.

(6) Both hot and cold water from an approved source shall be available at each lavatory and shower.

(7) Toilets shall be installed on (1) to a partitioned enclosure.

(8) Modesty offsets or fixed partition screens shall be provided at each entrance and exit.

09.8.3 Maintenance

(1) The campground, all of its facilities, and each campsite shall be kept clean, orderly and free of unhealthful conditions. Wash/toilet rooms and fixtures shall be cleaned and disinfected as often as necessary, but in no event less than three (3) times in every 24 hours.

09.8 CAMPGROUND REGULATIONS

09.8.3 Maintenance Continued

(2) Refuse containers shall be maintained within 300 feet of each campsite and have a capacity equivalent to at least thirty (30) gallons volume per site. The containers shall have tight fitting covers and both the containers and covers shall be secured against dislodgment by small children or animals. Each container must be emptied daily and kept clean and sanitary.

(3) There shall be no poison ivy within two (2) feet of any area, way or path used, or intended to be used, by foot traffic.

09.8.4 Water

(1) Drinking and washing water shall be from an approved source.

(2) The discharge openings of all outside faucets shall be not less than three (3) feet above the ground. A gravel filled dry well or drain shall be provided for each outside faucet in such a manner as to prevent an accumulation of water from spillage.

(3) An outside drinking water faucet, located away from wash/toilet rooms and refuse containers, shall be provided for every twenty (20) sites or fraction thereof.

09.8.5 Emergency Provisions

(1) An employee knowledgeable in emergency procedures shall be in attendance at all times. An office, equipped with a telephone, shall be maintained in a permanent structure.

(2) A public telephone, accessible at all times to campground customers, shall be maintained and therewith shall be prominently displayed emergency phone numbers, including that of the Board of Health.

(3) Infectious or contagious conditions, septic system failure and surfacing of septic/sewage effluent shall be reported immediately to the Board of Health.

8/5/80